

MODEL 405260-903

NSN: 6130-01-408-4656

Behlman's 405260-903 COTS EMDU Power Supply is a highly reliable, switch mode units built for high-end industrial or Military applications. The EMDU Supply can accept a three phase 115/200 VAC, 400 Hz input and can supply eight DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications, and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Unit is air cooled.

INPUT Input Transient protection per Mil-STD-704A
115/200 VAC +/- 20%, 360-440 Hz

OUTPUT:

- | | |
|----|------------------|
| 1. | +5 VDC @ 45 A |
| 2. | -5.2 VDC @ 6 A |
| 3. | -2 VDC @ 1.5 A |
| 4. | +60 VDC @ 0.1 A |
| 5. | +6.3 VDC @ 0.5 A |
| 6. | +15 VDC @ 5 A |
| 7. | -15 VDC @ 4 A |
| 8. | +28 VDC @ 4.5 A |
- Load Regulation:** 1.0% no load to full load at nominal line.
Line Regulation: 0.1% for 10% line change.



PARD-Ripple & Noise: 1% of output voltage p-p maximum. (0.1-10 MHz bandwidth)

Over voltage protection: 130% max.

Short circuit protection: Included

Current Limit: Constant current limited to 130% of rated current max.

Efficiency: 75%.

GENERAL CHARACTERISTICS

Isolation

Input to Output: 1000 VDC

Input to Case: 1000 VDC

Output to Case: 200 VDC

Dimensional Data: 11.5"L X 8.75"W X 4.0"H

Weight: 13.5 lbs

Input: M24308/4-1W

Output: M24308/6-15

ENVIRONMENTAL:

Operating Temperature: -40°C to 90°C case temperature

Storage Temperature: -57°C to 85°C

MTBF 90,000 @ 25 Degrees C base plate, Ground benign

Designed to meet the following MIL Standards

Shock: MIL-S-901; MIL-STD-810C

Vibration: MIL-STD-167; MIL-STD-810C; RTCA/DO-160

Humidity: MIL-STD-810C

EMI/EMC: MIL-STD-461C/D; RTCA/DO-160. RE102 with proper shielding.

Input power: MIL-STD-704A



www.behlman.com



Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

2363 Teller Road, Suite 108
Newbury Park, CA 91320
805 375-7046 800 456-2006
Fax: 805 498-2147

sales@behlman.com