Behlman Power Products

COTS POWER SUPPLY

MODEL 405260-903 NSN: 6130-01-408-4656

Behlman's 405260-903 COTS EMDU Power Supply is a highly reliable, switch mode units built for high-end industrial or Military applications. The EMDU Supply can accept a three phase 115/200 VAC, 400 Hz input and can supply eight DC outputs. These rugged power supplies are built to support the rigor of airborne, shipboard and mobile applications, and designed to meet the input power requirements of MIL-STD-704 and RTCA-DO160. Unit is air cooled.

INPUT Input Transient protection per Mil-STD-704A

115/200 VAC +/- 20%, 360-440 Hz

OUTPUT:

Load Regulation: 1.0% no load to full load at nominal line.

Line Regulation: 0.1% for 10% line change.

PARD-Ripple & Noise: 1% of output voltage p-p maximum. (0.1-10 MHz bandwidth)

Over voltage protection: 130% max. Short circuit protection: Included

Current Limit: Constant current limited to 130% of rated current max.

Efficiency: 75%.

GENERAL CHARACTERISTICS

Isolation

Input to Output: 1000 VDC Input to Case: 1000 VDC Output to Case: 200 VDC

Dimensional Data: 11.5"L X 8.75"W X 4.0"H

 Weight:
 13.5 lbs

 Input:
 M24308/4-1W

 Output:
 M24308/6-15

ENVIRONMENTAL:

Operating Temperature: -40°C to 90°C case temperature

Storage Temperature: -57°C to 85°C

MTBF 90,000 @ 25 Degrees C base plate, Ground benign

Designed to meet the following MIL Standards
Shock: MIL-S-901; MIL-STD-810C

Vibration: MIL-STD-167; MIL-STD-810C; RTCA/DO-160

Humidity: MIL-STD-810C

EMI/EMC: MIL-STD-461C/D; RTCA/DO-160. RE102 with proper shielding.





ORBIT POWER GROUP

www.behlman.com

Headquarters:

80 Cabot Court, Hauppauge, NY 11788 631 435-0410 800 874-6727

Behlman Electronics Fax: 631 951-4341

sales@behlman.com







Behlman Power Products

COTS POWER SUPPLY

Input power: MIL-STD-704A



www.behlman.com



Headquarters: 80 Cabot Court, Hauppauge, NY 11788 631 435-0410 800 874-6727 Fax: 631 951-4341

sales@behlman.com

